

COLOUR HARDENER

SYDNEY DECORATIVE CONCRETORS WAREHOUSE PTY LTD

Chemwatch: **4751-41** Version No: **2.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: **27/06/2017** Print Date: **14/02/2018** L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	COLOUR HARDENER	
Synonyms	Spray On Concrete Resurfacing (Part A), Base Modified (Part A), 1 PAC	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	To provide a hard coloured or multi coloured hardened surface to fresh concrete. Its main application is the first step in the production of stamped concrete
	and stencilled concrete. Also used for spray on applications.

Details of the supplier of the safety data sheet

Registered company name	SYDNEY DECORATIVE CONCRETORS WAREHOUSE PTY LTD		
Address	U2/1 Hargraves Place NSW 2164 Australia		
Telephone	02 97564688		
Fax	02 9756 4866		
Website	www.concretorswarehouse.com		
Email	admin@concretorswarehouse.com		

Emergency telephone number

Association / Organisation	Company Mobile
Emergency telephone numbers	0410 128 175
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		
Toxicity	0		0 = Minimum
Body Contact	1		1 = Low 2 = Moderate
Reactivity	0		3 = High
Chronic	0		4 = Extreme

Poisons Schedule	Not Applicable
Classification	Not Applicable
Label elements	
Hazard pictogram(s)	Not Applicable

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

SIGNAL WORD

NOT APPLICABLE

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

COLOUR HARDENER

Issue Date: **27/06/2017**Print Date: **14/02/2018**

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
Not Available	30-60	quartz sand	
Not Available	30-50	hydraulic binder	
Not Available	10-15	inorganic pigments (colour dependant)	
		cement	

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear. ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	If dust is inhaled, remove from contaminated area. Encourage patient to blow nose to ensure clear passage of breathing. If irritation or discomfort persists seek medical attention.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. 		
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. 		
HAZCHEM	Not Applicable		

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

methods and material for contaminent and cleaning up			
Minor Spills	 Clean up all spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator. Use dry clean up procedures and avoid generating dust. 		

Chemwatch: 4751-41 Version No: 2.1.1.1

Page 3 of 7

COLOUR HARDENER

Issue Date: 27/06/2017 Print Date: 14/02/2018

Major Spills

Moderate hazard

- ▶ CAUTION: Advise personnel in area.
- ► Alert Emergency Services and tell them location and nature of hazard.
- ► Control personal contact by wearing protective clothing.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- ▶ Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

Other information

- ▶ Store in original containers. ▶ Keep containers securely sealed.
- ▶ Store in a cool, dry area protected from environmental extremes.
- ▶ Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Lined metal can, lined metal pail/ can.
- ▶ Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.

Storage incompatibility

None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
COLOUR HARDENER	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
quartz sand	Not Available		Not Available	
hydraulic binder	Not Available		Not Available	
inorganic pigments (colour dependant)	Not Available		Not Available	

MATERIAL DATA

Exposure controls

Appropriate	engineering
	controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection









Eye and face protection

- Safety glasses with side shields.
- ▶ Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final

Hands/feet protection

Personal hygiene is a key element of effective hand care.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- ▶ polychloroprene.
- ▶ nitrile rubber
- butvl rubber.

Body protection

See Other protection below

Issue Date: **27/06/2017**Print Date: **14/02/2018**

Other protection

- Overalls.
- P.V.C. apron.
- Barrier cream.

Thermal hazards

Not Available

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

^{* -} Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Fine coloured powder; slightly soluble in water. 0-25% of particles are in the respirable range Available in various colours.		
Physical state	Divided Solid	Relative density (Water = 1)	2.85-2.9 (loose)
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	>1000	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Partly miscible	pH as a solution (1%)	>12.0
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if

Inhaled Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures

Chemwatch: **4751-41**Version No: **2.1.1.1**

Page 5 of 7 COLOUR HARDENER

Issue Date: **27/06/2017** Print Date: **14/02/2018**

O - Data Not Available to make classification

Legend: Acute Toxicity Skin Irritation/Corrosion	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained data extracted from RTECS - Register of Toxic Effect of chemical Substances Carcinogenicity Reproductivity	<u> </u>	
Legend:	data extracted from RTECS - Register of Toxic Effect of chemical Substances	·	
		d from manufacturer's SDS. Unless otherwise specified	
COLOUR HARDENER	'		
	Not Available Not Available		
COLOUR HARDENER	TOXICITY IRRITATION		
Chronic	Principal routes of exposure are by accidental skin and eye contact and inhalation of generated Overexposure to respirable dust may cause coughing, wheezing, difficulty in breathing and impedereased vital lung capacity, chest infections Repeated exposures, in an occupational setting, to high levels of fine- divided dusts may product lodgement of any inhaled dusts in the lung irrespective of the effect. This is particularly true who (1/50,000 inch), are present. Lung shadows are seen in the X-ray.	aired lung function. Chronic symptoms may include e a condition known as pneumoconiosis which is the	
Еуе	Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflar following direct contact, and/or produces significant inflammation when applied to the healthy ir being present twenty-four hours or more after the end of the exposure period. Skin irritation may may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopil layer of the skin (spongiosis) and intracellular oedema of the epidermis.	tact skin of animals, for up to four hours, such inflammation also be present after prolonged or repeated exposure; this skin redness (erythema) and swelling (oedema) which may	
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health).		

SECTION 12 ECOLOGICAL INFORMATION

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE SOURCE
COLOUR HARDENER	Not Available	Not Available	Not Available	Not Not Available Available
Legend:	(QSAR) - Aquati		Registered Substances - Ecotoxicological Informa Ecotox database - Aquatic Toxicity Data 5. ECETO ncentration Data 8. Vendor Data	

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

► Reduction

Page 6 of 7 COLOUR HARDENER

Issue Date: **27/06/2017**Print Date: **14/02/2018**

- ▶ Reuse
- ▶ Recvcling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	Y
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Y
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC—STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancel

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

Chemwatch: 4751-41 Page 7 of 7 Issue Date: 27/06/2017 Version No: 2.1.1.1 Print Date: 14/02/2018

COLOUR HARDENER